



NOTES
 TOLERANCES ± 0.5 U05
 COLOUR - AS SPECIFIED ON ORDER

TESTING
 SHALL BE IN ACCORDANCE WITH EN 124 : 1994, SECTIONS 8.2 TO 8.3.1 INCLUSIVE.
 COVER & FRAME TO BE TESTED AS A COMPLETE UNIT.
 A TEST LOAD OF 8kN SHALL BE APPLIED 3 TIMES THROUGH A $\phi 250$ mm.
 TEST BLOCK POSITIONED AT THE GEOMETRIC CENTRE OF THE UNIT.
 FINALLY A TEST LOAD OF 125kN SHALL BE APPLIED AND MAINTAINED FOR
 30 SECONDS (MINIMUM).
 MAXIMUM PERMANENT SET, MEASURED AFTER 5TH APPLICATION OF 8kN
 TEST LOAD SHALL BE 1/100 X CLEAR OPENING [6.0mm].

SECTION X - X

ALSO AVAILABLE IN EN124 C250 LOAD CLASS

<p><small>The drawing and test requirements of applicable material are not intended to be a substitute for the manufacturer's instructions and should be read in conjunction with the relevant product literature. The manufacturer's instructions should be read in full before use.</small></p>		<p>TITLE</p> <p>600 X 450 CLEAR OPENING EN124, B725, SINGLE SEAL MANHOLE FRAME</p>		<p>DATE</p> <p>8/3/04</p>	
<p>SCALE</p> <p>1:2.5</p>	<p>MATERIAL</p> <p>POLYPROPYLENE</p>	<p>DATE</p> <p>8/3/04</p>	<p>DESIGNER</p> <p>MDS</p>	<p>CHECKED</p> <p>JEB</p>	<p>DATE</p> <p>8/3/04</p>
<p>FOR ASSOCIATED COVER SEE DRAWING NUMBER PDS/C/0033-12</p>			<p>Forecourt Solutions</p>		
<p>Neovort Ground North Newton Somerset TA7 9BD</p>			<p>customer</p>		
<p>DRAWING NO.</p> <p>PDS/C/0035</p>			<p>DATE</p> <p>8/3/04</p>		